

NE  
method is preferably applied in the downlink of the FDD mode of UMTS mobile radio systems.

**In the claims:**

On page 13, cancel line 1, and substitute the following left-hand justified  
5 heading therefor:

**We Claim as Our Invention:**

Please cancel claims 1-10, without prejudice, and substitute the following claims therefor:

11. A method for transmitting data over a radio interface between a base  
10 station and a plurality of subscriber stations in a radio communication system, the method comprising the steps of:

distinguishing channels in a broadband frequency band using individual spread codes, wherein at least one common channel is allocated to a plurality of connections existing in parallel for use at successive times;

02  
10816048875860  
0957884-091801  
15 signaling in-band a subsequently valid allocation of the at least one common channel for one of the plurality of connections in at least one of the channels of the data transmission using a data rate allocated to the connection;

agreeing upon a relationship between the allocated data rate and the at least one common channel to be used in a separate signaling channel; and

20 transmitting the data in the at least one of the channels for data transmission based on the allocation.

12. A method for transmitting data over a radio interface between a base station and a plurality of subscriber stations in a radio communication system as  
25 claimed in claim 11, wherein, within one of the plurality of connections between the base station and a subscriber station, a combination of data for a plurality of services is transmitted within at least one channel, with each of the combination, the data rate and the allocation of the common channels being signaled using TFCI values.

30

13. A method for transmitting data over a radio interface between a base station and a plurality of subscriber stations in a radio communication system as claimed in claim 11, wherein the transmission of data occurs in a downlink direction from the base station to the plurality of subscriber stations.

5

14. A method for transmitting data over a radio interface between a base station and a plurality of subscriber stations in a radio communication system as claimed in claim 13, wherein a largest possible number of channels are allocated as the common channels, with at least one channel per connection being allocated

10 exclusively.

15. A method for transmitting data over a radio interface between a base station and a plurality of subscriber stations in a radio communication system as claimed in claim 14, wherein the common channels are allocated for connections

15 having a high maximum data rate.

16. A method for transmitting data over a radio interface between a base station and a plurality of subscriber stations in a radio communication system as claimed in claim 14, wherein the common channels are allocated for connections

20 having high data rate dynamics.

17. A method for transmitting data over a radio interface between a base station and a plurality of subscriber stations in a radio communication system as claimed in claim 11, wherein, for a subset of the data rates, the in-band signaling

25 can be used to select a plurality of combinations of channels for a connection.

18. A method for transmitting data over a radio interface between a base station and a plurality of subscriber stations in a radio communication system as claimed in claim 11, wherein a relationship between the allocated data rate and the

30 common channels to be used is agreed upon at connection setup.

A2  
cont

09857884 "091801